

Nippel 45° rörböj | 4095

KONSTRUKTION:

Nippel med 45° rörböj möjliggör effektiv riktning av flödet i rörsystem genom att ändra rörets vinkel vid 45 grader.

DKR 45° - BSP hona 45°, 60° kona

Dimensioner enligt skiss är angivna i mm.



Art nr.	Gänga BSP (F1)	Slang ID tum	Slang DN (mm)	CH	A	B	Antal
4095-0302	R 1/8	3/16	5	15	38	13	
4095-0304	R 1/4	3/16	5	19	40	16	
4095-0402	R 1/8	1/4	6	15	38	13	
4095-0404	R 1/4	1/4	6	19	41	16	
4095-0406	R 3/8	1/4	6	22	43	18	
4095-0504	R 1/4	5/16	8	19	53	17	
4095-0506	R 3/8	5/16	8	22	54	18	
4095-0604	R 1/4	3/8	10	19	55	17	
4095-0606	3/8	3/8	10	22	57	18	
4095-0608	R 1/2	3/8	10	27	60	21	
4095-0806	R 3/8	1/2	12	22	62	19	
4095-0808	R 1/2	1/2	12	27	65	22	
4095-0810	R 5/8	1/2	12	30	68	25	
4095-0812	R 3/4	1/2	12	32	69	26	

HYDRAULIKPRODUKTER | PRESSKOPPLINGAR | NIPPEL 45° RÖRBÖJ | 4095

4095-1010	R 5/8	5/8	16	30	77	25	
4095-1012	R 3/4	5/8	16	32	79	27	
4095-1212	R 3/4	3/4	19	32	82	26	
4095-1216	R 1"	3/4	19	38	84	28	
4095-1616	R 1"	1"	25	38	111	31	
4095-1620	R 1" 1/4	1"					
4095-2020	R 1" 1/4	1" 1/4					
4095-2424	R 1" 1/2	1" 1/2					
4095-2432	R 2"	1" 1/2					
4095-3232	R 2"	2"					